



AVAFLOOR.COM • 877.861.5292

AVA STYL GLUE DOWN TECHNICAL DATA

AVA STYL Luxury Vinyl Tile and Plank products have been tested in accordance with the following ASTM Standardized Tests and meet the listed specifications. AVA STYL is also available in 2G Clic.

PRODUCT CONSTRUCTION:	SOLID PVC VINYL WITH POLYURETHANE FINISH
OVERALL THICKNESS:	2.0MM
WEAR LAYER THICKNESS / TYPE:	8 MIL (0.20MM) SOLID PVC
INSTALLATION METHOD:	GLUE DOWN
SIZE AVAILABLE:	6" X 36" (STRAIGHT EDGE)
APPLICATIONS:	RESIDENTIAL, COMMERCIAL
WARRANTY:	10 YEAR RESIDENTIAL 3 YEAR LIGHT COMMERCIAL
RECOMMENDED ADHESIVE:	NOVALIS NFA-T226 TRANSITIONAL LV ADHESIVE NOVALIS NFA-S300 AEROSOL SPRAY ADHESIVE
ASTM F1700 SPECIFICATION:	CLASS III, TYPE B PRINTED FILM VINYL TILE/PLANK W/EMBOSSSED SURFACE
ASTM E648 CRITICAL RADIANT FLUX:	EXCEEDS CLASS 1 RATING PER NFPA LSC 101
ASTM E662 OPTICAL DENSITY OF SMOKE:	PASSES REQUIREMENT OF <450 SPECIFIC DENSITY
ASTM F970 STATIC LOAD, SINGLE WEIGHT:	RESIDUAL INDENTATION 0.003 INCH @ 250 POUNDS
STATIC LOAD, MODIFIED TESTING:	MEETS OR EXCEEDS 1,400 LBS.
ASTM D2047 STATIC COF:	EXCEEDS .50 SCOF
ASTM F137 FLEXIBILITY:	PASSES
ASTM F1514 RESISTANCE TO HEAT:	PASSES
ASTM F1515 RESISTANCE TO LIGHT:	PASSES
ASTM F925 RESISTANCE TO CHEMICALS:	PASSES
ASTM F386 SVF THICKNESS:	PASSES
ASTM F410 WEAR LAYER THICKNESS:	PASSES
ASTM F1914 RESIDUAL INDENTATION:	PASSES
ASTM F2055 SIZE & SQUARENESS OF TILE:	PASSES
ASTM F2199 DIMENSIONAL STABILITY:	PASSES



AVAFLOR.COM • 877.861.5292

HEALTH AND ENVIRONMENT:

100% PHTHALTE FREE, 100% VIRGIN VINYL
AVA DSGN TRANSPARENCY PORTFOLIO INCLUDES: HPD, EPD, DECLARE LABEL
REACH AND CE COMPLIANT, FLOORSCORE CERTIFIED

STYL PACKAGING:

STYL GLUE DOWN	
Pieces per Carton	24 pcs
Square Feet per Carton	36
Weight per Carton	25.89
Cartons per pallet	55
Square Feet per pallet	1,980.00
Weight per pallet includes pallet	1,474