OFFERED IN 38 COLORWAYS INCLUDING BRIGHTS AND NEUTRALS, **AVA SPRK** IS SUITABLE FOR VIRTUALLY ALL COMMERCIAL INSTALLATIONS WITH AN EMPHASIS ON THE HEALTHCARE AND EDUCATION SECTORS.



LIGHT LAGER

• WEAR LAYER: 20 MIL

• THICKNESS: 2.5 MM • SIZE: 18" X 18" STRAIGHT EDGE

• 100% PHTHALATE FREE

• WARRANTY: 10 YEAR COMMERCIAL & LIFETIME RESIDENTIAL

AMP COATING: ANTI-MICROBIAL, INCREASED SCRATCH AND SCUFF RESISTANCE, EXCELLENT STAIN AND FADE RESISTANCE, EASY TO CLEAN, NO NEED TO WAX

TRANSPARENT WEAR LAYER: EXTREMELY DURABLE

HIGH PERFORMANCE VINYL MIDDLE LAYER: PROVIDES EXTRA STABILITY AND DURABILITY

VINYL BACKING LAYER: HIGH RESISTANCE TO PRESSURE AND ECO-FRIENDLY PERFORMANCE

AVAILABLE IN THE GLUE DOWN CONSTRUCTION, AVA SPRK IS THE PERFECT LONG-TERM FLOORING SOLUTION FOR HEAVY TRAFFIC AREAS INCLUDING AREAS WITH ROLLING LOADS.







AVA SPRK

TILE SIZE: 18" X 18"



SPECIFICATIONS: ASTM F1700-13 SOLID VINYL FLOOR TILE: CLASS III, TYPE B ASTM D2047 STATIC COF FOR POLISHED SURFACES: EXCEEDS INDUSTRY STANDARDS ASTM F970-07 STATIC LOAD LIMIT: PASSES (MODIFIED EXCEEDS 1000 LBS PSI) ASTM E648 CRITICAL RADIANT FLUX: CLASS 1 PASSES ASTM E662 SMOKE DENSITY: EXCELLENT ASTM F925 STAIN & CHEMICAL RESISTANCE:

















