

CN Loose Lay Tile (LLT) Novalis Innovative Flooring

Final Assembly: Zhenjiang, Jiangsu, China

Life Expectancy: 10 Years Commercial, 25 Years Residential

Year(s)

Embodied Carbon: 8.75E+00 kg CO2 eq **Declared Unit:** 1 Meter Squared of Tile

End of Life Options: Salvageable/Reusable in its Entirety,

Recyclable (100%)

Ingredients:

Filler: Calcium carbonate; PVC: Polyvinyl chloride; Plasticizer: Octadecaneoic Acid, 10-Chloro-9-Methoxy, Methyl Ester; Dioctyl Terephthalate, DOTP; Fire retardant: Magnesium hydroxide; Glass Fiber; Stabilizer: Epoxidized soybean oil; Calcium stearate; Zinc Stearate; PU Coating: Epoxy Acrylate; Hexamethylene Diacrylate; 2-Hydroxyethyl methacrylate; Dipropylene Glycol Diacrylate; Propoxylated Neopentyl Glycol Diacrylate; Trimethylol Propane triacrylate; Tripropylene glycol diacrylate; 2,4,6-Trimethyl Benzoyl Diphenyl Phosphine Oxide; 2-Hydroxy-2-Methyl-Phenyl-Propan-1-One; Pigment: Carbon black

Living Building Challenge Criteria:

I-13 Red List:

☐ LBC Red List Free

☐ LBC Red List Approved

% Disclosed: 100% at 100ppm VOC Content: Not Applicable

■ Declared

I-10 Interior Performance: CDPH Standard Method v1.1-2010

I-14 Responsible Sourcing: Not Applicable

NOV-0003 EXP. 01 APR 2023 Original Issue Date: 2016