### **RYSE<sup>™</sup>** Specifications

- Wear Layer: 12 mil (0.30 mm)
- Overall Thickness: 2.0 mm
- Size: 6" x 48" (152 mm x 1219 mm)
- 100% Phthalate Free
- Reach Compliant
- Warranty: Lifetime Residential, 10-Year Heavy Commercial
- Patented Coating • 30% More Scratch Resistance Over Typical Coatings
  - Exceptional Wear Resistance and High Strength
  - Low-gloss finish

Vinyl backing layer with high resistance to pressure	Middle vinyl layer for extra stability and support	Printed layer to recreate the look and texture of natural materials	Transparent vinyl wear layer that's extremely durable	AMP PU coating for added scratch, stain, scuff, abrasion and fade resistance
			1	TANANA
AN /A				
ilue Down	LVT			
	layer with high resistance to pressure	layer with high resistance to pressure	layer with high resistance to pressure	layer with high resistance to pressure for extra stability and support and texture of natural materials wear layer that's extremely durable

ASTM F1700 SOLID VINYL TILE:	CLASS III, TYPE B
ASTM F2055 SIZE:	PASSES, $\pm$ 0.4 MM
ASTM F387 THICKNESS OF RESILIENT FLOORING:	PASSES, $\pm$ 0.13 MM
ASTM F2055 SQUARENESS:	PASSES, $\pm$ 0.25 MM
ASTM F1914 RESIDUAL INDENTATION:	PASSES, $\leq 0.2$ MM
ASTM F137 FLEXIBILITY:	PASSES, 25.4MM MANDREL
ASTM F2199 DIMENSIONAL STABILITY:	PASSES, < 0.5 MM / LIN. FT.
ASTM F925 CHEMICAL RESISTANCE:	PASSES ASTM F1700 REQUIREMENTS
ASTM F1514 HEAT COLOR STABILITY:	PASSES, $< \Delta E 8$
ASTM F1515 LIGHT COLOR STABILITY:	PASSES, $< \Delta E 8$
ASTM F970 STATIC LOAD (MODIFIED):	≤ 0.4 MM INDENT, 1600 LBS.
ASTM E648 (NFPA 253) CRITICAL RADIANT FLUX:	CLASS I, >0.45 W/CM <sup>2</sup>
ASTM E662 (NFPA 258) SMOKE DENSITY:	PASSES, <450
ASTM D2047 / UL 410 SLIP RESISTANCE:	> 0.5 SCOF (NO RAMPS)

### 

AVA<sup>®</sup> and RYSE<sup>™</sup> are trademarks of Novalis<sup>®</sup> Innovative Flooring.

f 🎔 💿 in avaflor.com • 877.861.5292 sales@avaflor.com



With worldwide sales offices and distribution partners, AVA is a leader in the design and manufacturing of innovative and sustainable resilient flooring. Established in 1984, AVA has developed a diverse range of designs and products that have won numerous awards and are recognized by the industry as setting the benchmark in LVT.

© 2024 Novalis<sup>®</sup> Innovative Flooring







**T**P

# AVA RYSE

## AVA RYSE



With 10 popular wood looks and realistic embossed surface, AVA° RYSE™ provides superior beauty and performance in 6" x 48" glue-down planks with a straight edge

AVA°'s proprietary AMP Advantage coating nakes RYSE™ the perfect solution for your heavy-traffic areas, including areas with heavy rolling loads. RYSE<sup>™</sup> is the ideal flooring for corporate offices, retail spaces, hospitality and a variety of other commercial environments.







Alpine Oak Khaki

AO005S-203K



Alpine Oak Anchor

AO009S-203K



Tuscany Oak Snow



Tuscany Oak Mist



Tuscany Oak Medallion







Peninsula Oak Plains



Tuscany Oak Peanut



TO001S-203K

TO002S-203K

TO009S-203K

PO002S-203K

PO004S-203K

TO008S-203K



Baltic Oak Taupe



Baltic Oak Suede



BO002S-203K

BO003S-203K